PERMATENT®

20 WIDE 8' SIDE WALLS

American Pavilion's wide selection of premium products includes highly durable and flexible clearspan PERMATENTS® that can be used in a variety of ways to best meet the needs of our customers.

Engineered for maximum strength with the ability to withstand strong winds and inclement weather, these clear span tents are constructed using a rigid, anodized aluminum frame covered with flameresistant vinyl fabric. With no center poles or exterior guy-lines, PERMATENTS® are extremely versatile. Designed in a modular system, these clear span tents can be expanded in ten foot lengths making them ideal choices for large exhibits or events.

Clearspan tents have a number of customizable features such as clear roof panels and side walls, varying perimeter heights and specialized sidewalls that can be easily opened or completely removed.

Interior rafters can be utilized for hanging signs, lights, fans, curtains or decorations. A full complement of flooring, lighting, glass doors, temperature control and generators is also available.

Quickly installed and removed, the clearspan PERMATENT® is an excellent choice for all occasions and events.




1706 Warrington Avenue Danville, Illinois 61832

800-424-9699

www.americanpavilion.com

217-443-0800 | Fax: 217-443-9619



Specifications

	8.4
US ¹	Metric
20°	20°
8' 7/16"	2450mm
11' 6"	3505mm
9' 10"	3000mm
4" x 1-3/4"	100mm x 48mm
3" x 2"	76mm x 50mm
2" x 1-1/2"	50mm x 38mm
Class C 90 mph winds	Class C 145 km/h winds
400 lbs	181kgs
	8' 7/16" 11' 6" 9' 10" 4" x 1-3/4" 3" x 2" 2" x 1-1/2" Class C 90 mph winds

The PERMATENT® is in accordance with all US building code standards including IBC2009

¹US measurements are approximate.

²Weight per rafter. Weight has to be equally distributed over the complete width of the rafter. All figures are theoretical calculations, based on a fully enclosed structure.

PERMATENT®

20 WIDE 10' SIDE WALLS

American Pavilion's wide selection of premium products includes highly durable and flexible clearspan PERMATENTS® that can be used in a variety of ways to best meet the needs of our customers.

Engineered for maximum strength with the ability to withstand strong winds and inclement weather, these clear span tents are constructed using a rigid, anodized aluminum frame covered with flameresistant vinyl fabric. With no center poles or exterior guy-lines, PERMATENTS® are extremely versatile. Designed in a modular system, these clear span tents can be expanded in ten foot lengths making them ideal choices for large exhibits or events.

Clearspan tents have a number of customizable features such as clear roof panels and side walls, varying perimeter heights and specialized sidewalls that can be easily opened or completely removed.

Interior rafters can be utilized for hanging signs, lights, fans, curtains or decorations. A full complement of flooring, lighting, glass doors, temperature control and generators is also available.

Quickly installed and removed, the clearspan PERMATENT® is an excellent choice for all occasions and events.




1706 Warrington Avenue Danville, Illinois 61832

800-424-9699

www.americanpavilion.com

217-443-0800 | Fax: 217-443-9619



Specifications

US¹	Metric
20°	20°
9' 4"	2845mm
12' 10"	3911mm
9' 10"	3000mm
4" x 1-3/4"	100mm x 48mm
3" x 2"	76mm x 50mm
2" x 1-1/2"	50mm x 38mm
Class C 90 mph winds	Class C 145 km/h winds
400 lbs	181kgs
	20° 9' 4" 12' 10" 9' 10" 4" x 1-3/4" 3" x 2" 2" x 1-1/2" Class C 90 mph winds

The PERMATENT® is in accordance with all US building code standards including IBC2009

¹US measurements are approximate.

²Weight per rafter. Weight has to be equally distributed over the complete width of the rafter. All figures are theoretical calculations, based on a fully enclosed structure.